

Four things worth remembering about Walther

Industrial power connection, from the plug on the machine to the distribution feeding it. Built in Somerset, New Jersey.



1 Power drops that arrive finished

Plug landed, cable or conduit cut to length, the listing carried by the assembly. **30, 60 and 100 A** pin and sleeve, nothing built in the field.



2 Connect, disconnect, lock out: one part

The receptacle and the switch are one unit: the circuit cannot be made or broken under load, and the handle takes a lock. **IP67 sealed where the water hits.**



3 The machine splits here

Procon rectangular connectors carry power and control through one hood. Mate the inserts, snap the hood, energize. **Washdown versions to IP68.**



4 30/60/100 A to the point of use

Distribution assemblies with breaker protection built in, shipped wired and ready. **One incoming feed** in place of a row of conduit runs.

Wrote the original IEC 60309 standard

Every pin and sleeve device is interchangeable with any conforming maker worldwide.

UL Listed and CSA Certified together

Series II ratings 20/30/60/100 A at 125/250/277/480 V. One part number covers a US or Canadian project.

US operation ISO 9001:2015

The Somerset, NJ assembly shop holds its own certification (TUV Rheinland, July 2026), a qualified supplier of record.

Your local Walther contact in Northern California and Northern Nevada

Jeff Weseloh, Application Engineer, Dynamic Measurement and Control Solutions
(408) 780-9190 · jeff@dynamicrep.com · www.dynamicrep.com/walther-werke